

(12) United States Patent

Ichikawa et al.

(10) Patent No.:

US 6,307,837 B1

(45) Date of Patent:

Oct. 23, 2001

(54) METHOD AND BASE STATION FOR PACKET TRANSFER

(75) Inventors: Takeo Ichikawa; Hidetoshi Kayama; Hiroyuki Yamamoto; Hitoshi

Takanashi; Masahiro Morikura, all of

Tokyo (JP)

(73) Assignee: Nippon Telegraph and Telephone

Corporation (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/132,148

(22) Filed: Aug. 10, 1998

(30) Foreign Application Priority Data

Aug. 12, 1997	(JP) 9-228966
(51) Int. Cl. ⁷	H04L 1/00
(52) U.S. Cl.	

380/283; 709/227; 713/153, 160, 161, 201; 370/230, 401

370/230,

(56) References Cited

U.S. PATENT DOCUMENTS

5,124,984 5,199,072 5,638,448	*	3/1993	Engel	. 380/44
5,659,615	*	8/1997	Dillon	380/270
5,689,566	*	11/1997	Nguyen	. 380/29
5,757,924	٠	5/1998	Friedman et al	380/283
5,790,548	*	8/1998	Sistanizadeh et al	370/401
6,047,325	*	4/2000	Jain et al.	709/227
6,081,900	+	6/2000	Subramaniam et al	713/201

FOREIGN PATENT DOCUMENTS

2-302139 12/1990 (JP) .

5-327773 12/1993 (JP) . 7-79243 A 3/1995 (JP) . 9-252323 A 9/1997 (JP) .

* cited by examiner

Primary Examiner—Salvatore Cangialosi (74) Attorney, Agent, or Firm—Pennie & Edmonds LLP

(57) ABSTRACT

A method of packet transfer is provided to resolve the problem of fraudulent access to user LANs through falsified source address so that only those pre-registered terminals are permitted to transfer packets with specific data networks. Each user LAN is assigned an identifier to identify respective user LAN beforehand. Packet network stores terminal information including terminal addresses, identifiers assigned to one and more user LANs that are permitted to communicate with each packet terminal and information necessary for terminal authentication beforehand. When the packet terminal starts a communication through a base station, the packet network authenticates the packet terminal, and if it is an unauthorized terminal, the packet network informs a denial for communication to the packet terminal. If an allowance for communication is obtained by authentication, the packet terminal encrypts data to be transmitted and sends a packet to the packet network with an attachment containing the encrypted data, identifiers for the selected user LAN among one and more user LANs, the destination address and the source address. Packet network receives the packet, and while decoding the encrypted data included in the received packet, detects tampering, and if tampering is detected, the received packet is discarded, but if there is no tampering, it checks whether the identity of source address and the identifier is registered in the terminal information, and if the identity is registered, the received packet is sent to the destination address, and if the identity is not registered, the received packet is discarded.

24 Claims, 22 Drawing Sheets

